



ELECTRIC DRYER MODELS	SubliPro 2414 9" Openings	SubliPro 3626 9" Openings	SubliPro 4827 9" Openings
product item number	71010	71004	71007
Service Voltage	380V/415V 3-Ph	380V/415V 3-Ph	380V/415V 3-Ph
Amps per phase	26 Amps @ 380V 3-Ph 28 Amps @ 415V 3-Ph	51 Amps @ 380V 3-Ph 56 Amps @ 415V 3-Ph	90 Amps @ 380V 3-Ph 100 Amps @ 415V 3-Ph
KW / BTU @ 380V	13.8 KW / 47,058	33.6 KW / 114,576 BTU	55.2 KW / 188,200 BTU
KW / BTU @ 415V	15.0 KW / 51,150 BTU	40.3 KW / 137,423 BTU	57.6 KW / 196,400 BTU
Unit Length Total	14' (427cm)	26' (792cm)	27' (823cm)
Unit Width Total	32" (81cm)	44" (112cm)	57" (145cm)
Oven Unit Height Total	50" (127cm)	50" (127cm)	50" (127cm)
Cooler Unit Height Total	74 1/4" (188.6cm)	74" (188cm)	74" (188cm)
Belt Width	24" (61cm)	36" (91cm)	48" (122cm)
Oven Length	60 Inches	132 Inches	132 Inches
"Dead" conveyor space between oven and cooler	12" (30.5cm)	12" (30.5cm)	12" (30.5cm)
Conveyor Entrance Length	24" (61cm)	36" (91cm)	36" (91cm)
Conveyor Exit Length	24" (61cm)	36" (91cm)	36" (91cm)
Fume Hood	6" (15cm) each end	12" (30cm) each end	12" (30cm) each end
Oven Throat / Door Openings	9" (22.8cm)With Curtains	9" (22.8cm)With Curtains	9" (22.8cm)With Curtains
Belt Speed Control	Digital	Digital	Digital
Belt Type	Stainless Steel	Stainless Steel	Stainless Steel
Belt Direction Facing Control Box	Right to Left	Right to Left	Right to Left
Temperature Control - Type	Digital - West 6100	Digital - West 6100	Digital - West 6100
Number of Temp Control Zones	1 Zone	2 Zones	2 Zones
High / Low Temp Alarm?	No	No	No
Relay Lights	Yes - 3	Yes - 6	Yes - 9
Heater Lights	Yes - 6	Yes - 12	Yes - 18
Heater Overload Protection	Snapax-Rocker	Snapax-Rocker	Snapax-Rocker
Control Overload Protection	Snapax-Rocker	Snapax-Rocker	Snapax-Rocker
Number of Heaters	6 - 2,500W Finned Strip	12 - 3,200W Finned Strip	18 - 3200W Finned Strip
Maximum Operating Temperature	450F/232C	450F/232C	450F/232C
Recirculating Airflow	Yes - Variable	Yes - Variable	Yes - Variable
Number of Recirculating Air Zones	1 Zone	2 Zones	2 Zones
Recirculating Airflow speed	1500 CFM	3000 CFM	6000 CFM
Exhaust Duct Size	8" (20.3cm)	10" (25.4cm)	10" (25.4cm)
Exhaust CFM @ 60 Hz	350 CFM	1000 CFM	1000 CFM
Chimney None/Fixed/Variable	Fixed	Fixed	Fixed
Backdraft Flapper?	Yes	Yes	Yes
Cooler Section	Yes	Yes	Yes
Cooler Length	3' (91cm)	6' (183cm)	7' (213cm)
CFM	1550	4400	5500
Wheels on Legs	Yes	Yes	Yes
Insulation under top skin	Yes	Yes	Yes
Certifications ETL/CE/CSA	CE	CE	CE
PRODUCTION CAPACITY PER HOUR: Mugs placed on 6" centers down the belt 4 wide on 24" belts, 6 wide on 36" belts and 7 wide on 48" belts with 12 minute retention time inside oven. Note: Actual output will depend on ink requirement of retention time in the oven, temperature set and efficiency of operator loading the belt.	120-180 per hour	300-500 per hour	750-1100 per hour
Shipping Crate Dimensions			
Main Body:	293 x 103 x 128cm	460 x 143 x 140cm	
Cooler & Extension:	203 x 103 x 143cm	325 x 143 x 140cm	
Shipping Crate Weight			
Main Body:	453Kg	1,088Kg	Ships fully assembled in a dedicated 40ft container
Cooler & Extension:	227Kg	453Kg	
Shipping Method	Shipped & delivered in a dedicated 20ft container	Shipped & delivered in a dedicated 40ft container	